

Foremay EC188™ M-SERIES

TYPICAL SPECIFICATIONS

Operating temperature: from 0 ~ +55°C to -40 ~ +85°C

Specifications

Form factor	R/W Speed, max. (MB/s)	Capacity	Optional features
PCIe x8 Gen.3.0	3,800/3,100	1 TB ~ 8 TB	S1, HE
PCIe x8 Gen.2.0	2,400/2,000	1 TB ~ 6 TB	S1, HE
PCIe x4 Gen.2.0	1,500/1,400	2 TB ~ 12 TB	S1, HE, OP
PCIe x4 Gen.1.0	800/700	2 TB ~ 32 TB	S1, HE
PXle / CPCle	3,800/3,100	1 TB ~ 8 TB	S1, HE
VPX	3,800/3,100	1 TB ~ 8 TB	S1, HE
2U Rackmount	1 million IOPS	24 TB ~ 200 TB	S1, HE
2.5" SFF-8639 NVMe	1,600/1,500	1 TB ~ 8 TB	S1, HE, OP
2.5" SAS	550/400	500 GB ~ 2 TB	S1, HE, SC
2.5" SATA III	550/510	500 GB ~ 8 TB	S1, HE, SC
3.5" SATA III	550/510	1 TB ~ 8 TB	S1, HE, SC

Optional feature code

S1: Type-I secure erase, software or firmware bases secure erase

HE: Hardware based encryption

CC: Conformal coating

SC: Super capacitor

SC: TCG-Opal

Custom design

Please contact us if your required special feature is not listed here.

We can design and build a customised product for you.