

Industrial DIN Rail Mount 10 /100BASE-TX Ethernet Copper Extender EIR2-EXTEND



PRODUCT FEATURES

- Hardened 10/100BASE-TX Ethernet Extender
- Extend Ethernet Copper up to 2200 meters (7218 feet) over existing copper wire (common copper, telephone, Cat5e)
- VDSL2 technology with transmission rate of 100Mbps at 400meters
- -40°C to 75°C (-40°F to 167°F) operating temperature range
- Auto -detection of Local/Remote function to reduce installation time
- Local/Remote function to reduce installation time
- Link-Down-Relay (LDR) function to inform link loss to other side
- One 10/100Base TX (TX) Ethernet port with RJ-45 connector
- IEEE 802.3 10BaseT and IEEE 802.3u 100BaseTX compliant
- Line port uses common RJ-11 connector

ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION
EIR2-EXTEND	Industrial DIN rail mount 10/100BASE-TX Ethernet Extender, VDSL2

ACCESSORIES

- MDR-40-24 - DIN Rail Power supply 24VDC 40 Watt
- C5UMB3FBL - 3 ft. (1 M) - Blue - Category 5e UTP Patch Cord

The model EIR2-EXTEND extends your copper Ethernet connections up to 2200 meters (7218 feet) over twisted pair wire. The Ethernet Extender fully complies with IEEE 802.3 10BaseT and IEEE 802.3u 100BaseTX standards. Two EIR2-EXTEND models are required for the Ethernet extension, (one at each end of your extension points). The EIR2-EXTEND's hardened design features high shock and vibration, electrical noise immunity, a wide operating temperature range from -40°C to 75°C, and ruggedized aluminum housing. The EIR2-EXTEND is the ideal Ethernet extender for environments where connectivity is crucial. External power supplies are required (not included).

Industrial DIN Rail Mount 10 /100BASE-TX Ethernet Copper Extender

EIR2-EXTEND



SPECIFICATIONS

TECHNOLOGY

Standards	IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE802.3x
Protocols	Transparent to higher layer protocols
Processing Type	Half-duplex back-pressure and IEEE802.3x Full-duplex flow control
Forward and Filtering Rate	14,880pps for 10Mbps; 148,810pps for 100Mbps

INTERFACE

Ethernet Port	Port: One RJ-45 port <ul style="list-style-type: none"> Speed: 10/100Mbps Distance: 100 meters (328ft.) Cable: 10BASE-T: UTP CAT. 3, 4, 5 (2-pair wire) 100BASE-TX: UTP CAT. 5 (4-pair wire)
Extender Port	Port: One RJ-11 and Terminal Block port <ul style="list-style-type: none"> Speed: Up to 100Mbps Distance: up to 2600 meters (8530 ft.) Cable: Telephone wire 24 AWG (0.5mm diameter, 1-pair wire) or larger

DIP Switch

DIP 1 Site: Auto/Loc
DIP 2 LDR: ON/OFF

LED Indicators

Per Unit: Power 1, 2
Per 10/100TX Port: Link/Activity, Full-duplex
Line Speed: 100/80/60/40/20Mbps and Link below 20Mbps

POWER

Input Voltage	12 to 48VDC (Terminal Block)
Power Consumption	4.56W max. 0.38A @ 12VDC - 0.07A @ 48VDC
Protection	Over current protection Reverse polarity protection

MECHANICAL

Enclosure	Aluminum case IP30
Dimensions	42mm (W) x 90mm (D) x 100mm (H) (1.65" (W) x 3.54" (D) x 3.94" (H))
Weight	0.41 Kg (0.9 lbs.)
Installation	DIN-Rail (Top hat type 35mm) mounting

ENVIRONMENTAL

Operating Temperature	-40°C to 75°C (-40°F to 167°F)
Storage Temperature	-40°C to 85°C (-40 to 185°F)
Ambient Relative Humidity	5% to 95% (non-condensing)

REGULATORY APPROVALS

ISO	Manufactured in an ISO9001 facility
Safety	UL60950-1, EN60950-1, IEC60950-1
EMI	FCC Part 15B, Class A VCCI Class A EN61000-6-4 EN61000-6-2 <ul style="list-style-type: none"> EN61000-4-2 (ESD Standards) EN61000-4-3 (Radiated RFI Standards) EN61000-4-4 (Burst Standards) EN61000-4-5 (Surge Standards) EN61000-4-6 (Induced RFI Standards) EN61000-4-8 (Magnetic Field Standards)
EMS	IEC60068-2-6 Fc (Vibration Resistance) IEC60068-2-27 Ea (Shock)
Environmental	FED STD 101C Method 5007.1 (Free fall w/ package)

PERFORMANCE

DISTANCE (M)	DATA RATE (MBPS)
300m (984 ft)	100
400m (1312 ft)	80
600m (1969 ft)	60
800m (2625 ft)	40
2600 m (8530 ft)	1

Note: All speed selections are Symmetrical on the DSL and Full-duplex on the Ethernet

The data rate will vary according to line quality

MECHANICAL DIAGRAM

