

# Foremay TC166™ U- SERIES

## TYPICAL SPECIFICATIONS

Operating temperature: 0 ~ +70°C to -40 ~ +85°C

### Specifications

Form Factor	R/W Speed, Max. (MB/s)	Capacity (GB)	Optional Features
2.5" SATA III	550/510	60 ~ 8,000	S1, CC, HE
2.5" SATA II	250/210	60 ~ 10,000	S1, CC, HE
1.8" micro SATA	550/510	60 ~ 480	S1, CC, HE
1.8" SATA	550/510	30 ~ 256	S1, CC, HE
3.5" SATA III	550/500	60 ~ 4,000	S1, CC, HE
2.5" IDE / PATA	100/80	60 ~ 1,000	S1, CC, HE
1.8" IDE / PATA	90/80	8 ~ 256	S1, CC, HE
CompactFlash	90/80	8 ~ 256	S1, CC, HE
CFast	320/180	30 ~ 128	S1, CC
1.8" ZIF	100/95	30 ~ 256	S1, CC, HE

### Optional feature code

S1: Type-I secure erase, software or firmware bases secure erase

HE: Hardware based encryption

CC: Conformal coating

SC: Super capacitor

SC: TCG-Opal

### Custom design

Please contact us if your required special feature is not listed here.

We can design and build a customised product for you.